

This drawing is the property of and may embody proprietary information owned by *GOOD-JOB*. It is provided under a confidential relationship for a specific purpose. The recipient agrees to use it only for such purpose and to return it to *GOOD-JOB* upon request.

该图所显示的专有信息及其归常州市国挂进出口有限公司所有(以下简称GJ)。该图仅供接受方参考使用,并对此图有保密义务。GJ保留对此图无条件回收的权利。

Technical drawing of a bolt with the following dimensions labeled:

- F (nom.): Nominal length of the bolt.
- D : Diameter of the bolt head.
- H : Height of the bolt head.
- E : Thickness of the washer.
- 100° : Angle of the conical part of the bolt head.
- P_{min} : Minimum pitch of the threads.
- W_{max} : Maximum width of the threads.

NOTES:

1. Material: Body&Mandrel - 304SSUS

材料：铆壳&钉芯 - 304不锈钢

2. Finish: Body&Mandrel- Natural Polished

表面处理: 铆壳&钉芯 - 本色抛光

01	6.4x13.5	$\phi 6.4^{+0.08}_{-0.15}$	$2.3^{+0.3}_{-0.5}$	13.5±0.5	$\phi 9.3^{+0.9}_0$	29	4.20	$\phi 6.6 \sim \phi 6.8$	4.5 ~ 7.5	7800N min.	10700Nmin.				
02	6.4x15.5			15.5±0.5					6.5 ~ 9.5		12700Nmin.				
03	6.4x17.5			17.5±0.5					8.5 ~ 11.5		min.	13700N			
04	6.4x19.5			19.5±0.5					10.0 ~ 13.0						
05	6.4x21.5	21.5±0.5	23.5±0.5	14.0 ~ 17.0	min.	13700N									
06	6.4x23.5														
No.	Size	D	E	F	H	P	W	Hole Size 钻孔直径	Grip Range 柳接范围	Tensile 抗拉强度	Shear 抗剪强度	Scale/比例: N/A	TOL. U.O.S. DECIMALS:± 0.05 ANGLES:±2° 未注尺寸公差, 线性尺寸:± 0.05 角度: ±2°		